

Warmup Steel Range - "A" Rated Pump/Mixer



The Warmup Steel Range "A" rated pump/mixer is designed to be lightweight and compact in order to connect directly onto a standard underfloor heating manifold without the need for extra brackets or support.

The control pack consists of a mixing valve, circulating pump, return elbow, manifold adapter and all the necessary seals. It will provide temperature controlled mixed water to your underfloor heating circuits providing a heat output of up to 14kW.

The "A" Rated pump will reduce power consumption considerably, help reduce noise from thermostatic valves and similar fittings and improve control of the system.

Features:

- Compact bolt on unit provides quick and easy installation
- Adjustable range of 35°C - 60°C
- Provides controlled mixed temperature water to underfloor heating pipes
- Controls flow temperature to +/- 2°C even with changing boiler flow and return temperatures
- The pump/mixer is nickel plated to match the stainless steel manifold
- The pump/mixer can be reversed when the blanking cap and pump union are reversed

Technical Data:

Max. static pressure	10 bar
Max. working temperature:	90°C
Adjustable control range:	35°C - 60°C
Factory pre-set	35°C (minimum)
Dimensions:	260x210x155mm
Valve body:	Gunmetal
Seals:	PTFE
O-Rings:	Silicone rubber
Spring:	Stainless steel

