

# Warmup - Primer

[ACC-WUPRIMER]



EN

## Description:

A ready to use, bond enhancing and solvent-free single component primer for the preparation of absorbent and non-absorbent floors and walls with or without surface heating. Ideal for use before laying Warmup Peel and Stick systems, levelling compounds and tile adhesives.

**Suitable Substrates:** Concrete; Cement Screeds; Anhydrite Screeds; Magnesite Screeds; Levelling Compounds; Timber; Metal; Tile Backer Boards; Terazzo floors; Natural Stone; Ceramic Tiles; Vinyl; Epoxy Paints, Epoxy Moisture Barriers; Water-Resistant Adhesive Residues; MSP's; Abraded Mastic asphalt.

Not suitable for use on PUR pre-coatings, melamine faced boards. Contacting substrates, adhesives and compounds must be free of migrating elements.

**Substrate preparation:** The substrate must be dry, frost-free, solid, weight-bearing and dimensionally stable. It must be free from contaminants that may impede adhesion such as dust, dirt, oil, grease, release agents, loose material or surface laitance. Heated surfaces must be switched off and allowed to cool back to ambient conditions before application. The substrate must comply with the applicable National Standards, Directives and Codes of Practice relating to its intended use.

**Application:** Shake well before use. Wear appropriate PPE. Apply a single coat evenly with a roller or brush, avoiding pooling. A non-slip surface is achieved after drying. For heavily absorbent, cementitious substrates this primer may be diluted with up to 20 % water, or with calcium sulphate screeds up to 5 % water. After use, clean tools with soap and water before the primer dries.

**Safety instructions:** Dispose of in accordance with applicable regulations. Keep out of reach of children! Instructions for the safe use of our products can be found on our safety data sheet on [www.warmup.co.uk](http://www.warmup.co.uk).

**Product contains:** Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]. May produce an allergic reaction. EU limit value for this product (cat. A/h Wb): 30 g/l (2010). This product contains less than 30 g/l VOC.

## Technical specifications:

**Typical Consumption:** 7-10 m<sup>2</sup>/kg

**Application Temperature:** >5°C

**Ideal Application Air Humidity:** 40% to 60%

**Drying time:** 15 min (absorbent), 30 min (non-absorbent).

**Shelf Life:** 12 Months in original container when kept out of direct sunlight and at temperatures between 5°C and 25°C, avoiding frost. Diluted product must be used on the day of dilution or discarded.

## Contact

**Warmup plc**

[www.warmup.co.uk](http://www.warmup.co.uk)

[uk@warmup.com](mailto:uk@warmup.com)

0345 345 2288

**Warmup plc** ■ 704 Tudor Estate ■ Abbey Road ■ London ■ NW10 7UW ■ UK

**Warmup GmbH** ■ Ottostraße 3 ■ 27793 Wildeshausen ■ DE

Warmup - IM - ACC-WUPRIMER - V1.2 2025-09-24\_EN