

HiDECK Overlay 18

Screed replacement system

Where applicable, can be used in place of traditional liquid screed or levelling compounds for a faster install.

Suitable with a variety of floor finishes

Directly accepts all types of floor covering, including tiles.



Low thermal resistance

Perfect for underfloor heating applications and is Robust Detail Treatment FFT4 compliant.

Suitable for all subfloors

Suitable for all types of steel, concrete and timber floors.

Overview

HiDeck Overlay18 is a high density overlay board for underfloor heating applications. It is ideal for flooring applications incorporating underfloor heating due to its high thermal conductivity which provides rapid reaction times, saving on running costs.

In addition, its density makes it perfect for a variety of acoustic applications.

HiDeck18 is ideal for use over Warmup Contura, Ultra-12 and Foil underfloor heating systems.

Technical specifications

Product Code	WDO-HIDECK18
Thickness	18 mm
Type and composition	Tongue and groove high density gypsum
Thermal resistance	0.045 m ² K/W
Board dimensions	600 x 1200 mm
Weight	21.6 kg/m ² ; 15.55 kg/board
Fire class	A1
Environmental Credentials	GWP <5 100% Recycled Gypsum Zero ODP

Contact

Warmup plc

www.warmup.co.uk
uk@warmup.com

T: 0345 345 2288
F: 0345 345 2299

Warmup plc ■ 704 Tudor Estate ■ Abbey Road ■ London ■ NW10 7UW ■ UK
Warmup GmbH ■ Ottostraße 3 ■ 27793 Wildeshausen ■ DE

Warmup

Warmup - TS - HiDECK Overlay 18 - V1.0 2022-09-15_EN